Low Power Signal Diodes






Features:

- · Surge overload ratings to 2 amperes peak
- Ideal for printed circuit board
- Mounting position : Any

Mini Melf



Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%

Maximum Ratings

Type Number	Symbol	Value	Unit		
Repetitive Peak Reverse Voltage	V_{RRM}	100	V		
Reverse Voltage	V _R	75	V		
Forward Repetitive Peak Current (Note 1)	I _{FRM}	500			
Average Forward Current	IF _(AV)	150	mA		
Peak Forward Surge Current tp = 1µs	I _{FSM}	2	Α		
Power Dissipation (Note 1)	P _d	500	mW		
Thermal Resistance Junction to Ambient Air (Note 1)	RθJA	350	K/W		
Operating and Storage Temperature Range	T _j , T _{STG}	-65 to +175	°C		



Low Power Signal Diodes




Electrical Characteristics

Type Number		Symbol	Minimum	Maximum	Unit
Forward Voltage	IF = 5 mA IF = 50 mA	V	0.62	0.72 1	V
Peak Reverse Current	$V_R = 20 \text{ V}$ $V_R = 20 \text{ V}, T_j = 150^{\circ}\text{C}$ $V_R = 75 \text{ V}$	I _R	-	25 50 5	-
Junction Capacitance	V _R = 0, f = 1 MHz	C _j	-	4	mA
Reverse Recovery Time	e (Note 2)	t _{rr}	-	4	-

Notes:


- 1. Valid provided that terminals are kept at ambient temperature
- 2. Reverse recovery test conditions: I_F = 10 mA, V_R = 6 V, I_{rr} = 0.1 × I_R , R_L = 100 Ω


Ratings and Characteristic Curves



Low Power Signal Diodes







Specification Table

V _{rrm} (V)	V _r (V)	I _{fsm} (A)	I _{frm} (mA)	I _f (mA)	I _f (av) (mA)	P _d (mW)	Package	Part Number
100	75	2	500	200	150	500	MiniMELF	LL4148

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.



